



Certified ISO 9001

## Genesis II Select Directional™

# QUICK START GUIDE



**This Quick Start guide explains how to set up your Decatur Genesis II Select Directional and use its key features. Once you're set up you can learn more about Decatur Radar at [www.DecaturElectronics.com](http://www.DecaturElectronics.com).**

### Steps

1. With all cables, antennas and the hand remote attached, plug the cigar plug of the radar into a powered 12VDC cigarette lighter receptacle in the patrol vehicle.
2. Press the PWR button on the hand-held remote to power up the radar unit. The radar will run through a brief self-test.
3. Press the ANT FRONT or REAR button to select the antenna from which you want the radar to transmit. Press the same ANT button when you wish to place the radar back into standby mode.
4. [OPT] Press and release the MODE button to quickly toggle between Moving Mode Opposite Direction and Moving Mode Same Direction. Press and hold the MODE button for two seconds to activate Stationary Mode.
5. [OPT] Press and hold the FAST button to select Faster Mode when you want to track the next strongest target going faster than the strongest.
6. If you are in the Moving Mode Same Direction setting and want to track a target that is traveling slower than the patrol vehicle, press and release the FAST button for Slower Mode.
7. To lock on a target speed, press the LOCK button. The target speed will transfer to the LOCKED window. The radar will continue to process speeds and display them in the TARGET window.
8. To clear a locked speed, press the LOCK button when an antenna is transmitting and no target is present.